



MOSAL FLOORING


Evoque ESP 6.0mm

Collections	Evoque	
Construction	Multilayer ESP with Attached IXPE Underlayment	
Class / ASTM F3261	Class III, Type B	
Attached Underlayment	IXPE	
Finish	Super Protect Plus Technology	
	U.S.	Metric
Nominal Dimensions	9 in w x 60 in l	22.8 cm w x 152 cm l
Actual Dimensions	9.09 in w x 60 in l	22.81 cm w x 152.40 cm l
Wear Layer Thickness	22 mil (0.055 in)	
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating Or Direct Glue	



Recommended Installation Method

Pieces per Carton	6 pcs
Area per Carton	22.50 sq ft
Weight per Carton	41 lbs



IXPE is a premium acoustical underlayment made up of sound dampening high-performance cross-linked foam with an overlapping film for extra moisture protection at its joints. The extra fine foam offers advanced moisture protections and shock absorption. Utilizing the Progressive Foam Technology (PFT), IXPE underlay is designed for supreme sound Reduction.

Progressive foam technology (PFT) designed for supreme sound reduction Extra fine, cross linked foam for advanced moisture protection and shock absorption Excellent for radiant heat floors Mold and mildew resistant Anti-crush technology for excellent performance and long life.

Coating	Martindale Pilling Tester / Test Weight (ISO12947)	Class	Martindale Pilling Tester / Test Weight (ISO12947)	Class	Conclusion
Super Protect Plus – Super Anti-micro-scratch Coating	4N	Class 1	38N	Class 1-2	Good-Performed

Waterproof and Damp-proof

As the main component of SPC flooring is limestone powder, it performs well with water and mildew will not happen even with high humidity.

Performance + Testing

Static Load (ASTM F970) Residual	Passes
Indentation (ASTM F1914) Resistance	Passes
to Heat (ASTM F1514) Resistance to	Passes
Light (ASTM F1515) Resistance to	Passes
Chemicals (ASTM F925) Smoke	Passes
Density (ASTM E662, Flaming Mode)	Passes
Radiant Panel (ASTM E648)	Passes, Class I

Warranties

20 Year Commercial Limited Warranty



MOSAL FLOORING

Evoque – ESP 6.0mm

Specifications

Collections

Construction	Evoque
Attached underlayment	Multilayer ESP with Attached IXPE Underlayment
Embossing	IXPE Embossed in register
Nominal dimensions	US units 9 in w x 60 in l (0.055 in) 9.09 in w 40 in l
Wear layer thickness	Super Protect Plus Technology 2 Micro-Beveled Edge
Actual width Actual length	Floating Or Direct Glue (ASTM C 1028-96) >0.65 (NALFA 3.2) avg. 0.0015% inter status (Class 4) 75 74
Finish Edge profile	(NALFA 3.8) Class 4
Installation Slip	(NALFA 3.3) no change, xenon colorfast - score = 5.0
Resistance Thickness	UV slight effect std (class 4)
Swell Impact Insulation	(NALFA 3.4) score = 6.0 (class 4)
Class	Greenguard Gold and Floorscore (ASTM 648) Class I (ASTM E662-17) <450
(IIC)	
Sound Transmission Class (STC)	
Impact Resistance	
Dimensional Tolerance	
Colorfastness	
Stain Resistance	
Iaq Certification	
Radiant Panel	
Nbs Smoke	
FloorScore®	Indoor Air Quality Certified to SCS-EC10.3-2014 Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.
Assure Certified™	Conforms to the Resilient Floor Covering Institute Rigid Core Flooring Certification Standard SCS-0011, Version 1-0 (May 2020); ASTM F3261-20 Standard Specification for Resilient Flooring in Modular Format with Rigid Polymeric Core; CDPH/EHLB Standard Method v1.2-2017; Individual and combined ortho-phthalates concentration below 1,000 ppm; Individual and combined heavy metals concentration below 100 ppm.
Indoor Air Comfort Gold	The product complies with Indoor Air Comfort Gold requirements for product type, version 7.0 (2020). 20 year limited commercial wear
Warranty	lifetime limited structure lifetime limited waterproof lifetime limited pet

